

THRASHER

2020 Wood County Aerial Triangulation And Ground Control Report

Prepared by:

Craig Fry, CP

The Thrasher Group

600 White Oaks Blvd.

Bridgeport, WV 26330

Phone: (304) 624-4108

cfry@thethrashergroup.com

The Thrasher Group (TTG) has successfully completed the aerial triangulation (AT) for the countywide spring flight.

Using semi-automatic analytical aerial triangulation procedures, TTG determined the exterior orientation parameters for each exposure in the photography that covers the project area.

The results of the final adjustments are sufficient to enable TTG to photogrammetrically produce orthophotos from the photography. The AT solution ensures that the project data will meet or exceed the accuracy expectation as outlined in the contract.

Ground Control

The ground control network was designed to provide a geometrically strong horizontal and vertical control system within the project area.

Sufficiently identified ground control points (GCPS) were surveyed within the block to provide horizontal and vertical control.

Aerial Photography

Aerial photography for the project was captured between March 26, 2020 and April 4, 2020.

The photography was acquired with an approximate 60 percent overlap and an approximate 30 percent side lap. The flight altitude of the photography was approximately 7,700 feet above mean terrain.

Airborne GPS

Airborne-GPS (ABGPS) data was captured during the acquisition of the aerial photography. An appropriate GPS antenna was mounted on each aircraft used on the project, and the relationship between the antenna phase centers and the camera perspective centers was then determined through close-range survey techniques. Dual frequency, geodetic quality receivers were utilized for the data collection.

The GPS data was post-processed, and the appropriate interpolations, transformations and reductions were applied to derive the camera's spatial position referenced to the World Geodetic System of 1984 (WGS84) at each instant of exposure.

Flight

The flight plan was comprised of 42 flight lines. The designed ground sample distance per pixel was 10 centimeters.

The block consisted of a total of 2,046 images.

A fully equipped aircraft was employed for the photographic mission. In the aircraft, the instrumentation utilized in the acquisition of aerial photography and ABGPS data comprised of a Zeiss DMC II aerial camera featuring forward motion compensation, and a GPS Novatel Span Receiver with a collection rate of one half-second.

During each flight, every exposure triggered by each camera was recorded in the associated GPS data file as an external event. A time stamp for each event later allowed the interpolation of the camera position at each instant or exposure.

Aerial Triangulation

Aerial triangulation is the simultaneous space resection of image rays projected and recorded at one source, the perspective center of the aerial camera. These image rays projected from two or more overlapping images (stereo-models) intersect at the corresponding ground location to determine the three-dimensional coordinates of each point measured. This collection of image rays is fit to known ground survey control in a simultaneous three-dimensional least squares adjustment. After the completion of this adjustment, coordinates of the 'unknown' ground points are derived by the intersection of the adjusted image points.

The aerial triangulation was performed utilizing the ground control and the airborne GPS-assisted techniques. These data are then introduced along with the reduced image coordinates, as observations, into a combined three-dimensional simultaneous least squares adjustment by bundles. This approach allows a substantial reduction in the amount of ground control required for the AT solutions.

The purpose of aerial triangulation is to densify horizontal and vertical control from relatively few ground control points (GCPs). Since obtaining GCPs is a relatively significant expense in any mapping project, AT procedures are used to reduce the amount of field survey required by extending control to all stereo-models.

Internal software checks were performed to detect gross errors in the photo measurements.


Bundle Adjustment

The surveyed control, along with the reduced image coordinates, served as input into the 'combined' block adjustment. Three-dimensional, simultaneous least squares adjustments by bundles, were undertaken using Match-AT bundle adjustment software. This bundle block adjustment software has proven to be a very rigorous and stable platform.

Nine control points were used to constrain the AT solution. The sigma naught is a significant indicator of the quality of the adjustment. The sigma value derived by the block adjustment is the root mean square of all photo measurement residuals for the entire block. The lower the sigma naught, the less tension within the AT solution. The sigma naught for this adjustment was 1.1 microns. The residuals of the control points from measured position to surveyed position are as follows:

Residual point x y z (ft.)

620104	0.020	-0.005	-0.003
620105	0.004	-0.018	-0.001
630106	0.062	-0.013	0.021
630107	0.023	0.011	-0.002
630111	-0.025	-0.022	0.018
630113	-0.015	0.009	0.013
630114	-0.037	0.074	-0.053
630115	-0.012	-0.042	0.008
630116	-0.020	0.006	-0.002



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.019 Vt Prec 0.034	Method: VRS
Date: 03-02-2020	
Location: Waverly, Pleasant Co, WV	

Point 0620104 - ACP 104

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 309257.246
Easting (ft): 1441190.724
Elevation (ft): 651.668



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.024 Vt Prec 0.037	Method: VRS
Date: 03-02-2020	
Location: Williamstown, Pleasant Co, WV	

Point 0620105 - ACP 105

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 334353.615
Easting (ft): 1418282.162
Elevation (ft): 633.361



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.172 Vt Prec 0.285	Method: GPS Static
Date: 03-03-2020	
Location: Bull Creek Rd, Pleasant Co, WV	

Point 0630106 - ACP 106

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 294430.169
Easting (ft): 1465669.585
Elevation (ft): 713.466



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.020 Vt Prec 0.028	Method: VRS
Date: 03-03-2020	
Location: SR50, Ritchie Co, WV	

Point 0630107 - ACP 107

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 279349.436
Easting (ft): 1468305.412
Elevation (ft): 1119.326



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES


GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.015 Vt Prec 0.029	Method: VRS
Date: 03-03-2020	
Location: Hughes River, Wirt Co, WV	

Point 0630111 - ACP 111

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 239173.600
Easting (ft): 1433241.937
Elevation (ft): 616.592



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.015 Vt Prec 0.027	Method: VRS
Date: 03-03-2020	
Location: Tuckers Creek Grant Hill, Wirt Co, WV	

Point 0630113 - ACP 113

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 206771.645
Easting (ft): 1385419.486
Elevation (ft): 1092.99



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.018 Vt Prec 0.027	Method: VRS
Date: 03-03-2020	
Location: Belleville, Wood Co, WV	

Point 0630114 - ACP 114

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 233107.200
Easting (ft): 1334094.472
Elevation (ft): 601.309



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.020 Vt Prec 0.030	Method: VRS
Date: 03-03-2020	
Location: Washington, Wood Co, WV	

Point 0630115 - ACP 115

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 281195.833
Easting (ft): 1350847.154
Elevation (ft): 639.549



THRASHER

ARCHITECTURE | ENGINEERING | FIELD SERVICES

GNSS CONTROL POINT LOCATION SHEET

Horizontal Datum: NAD 83	Vertical Datum: NAVD88
Projection: SPC WV North	Geoid: G12BUS
Precisions (ft): Hz Prec 0.016 Vt Prec 0.030	Method: VRS
Date: 03-03-2020	
Location: Mineral Wells, Wood Co, WV	

Point 0630116 - ACP 116

Detailed Description:
040-10259 BM5730 SPRING FLIGHT

Northing (ft): 258602.264
Easting (ft): 1393023.914
Elevation (ft): 658.703

