FLOOD RISK ASSESSMENT REPORT MORGAN COUNTY, WV



Supplement to 2017 Region 9 Planning and Development Council Multi-Hazard Risk Assessment and Mitigation Plan

October 31, 2016

Prepared by:

WV GIS Technical Center Department of Geology & Geography West Virginia University 330 Brooks Hall, PO Box 6300 Morgantown, WV 26506



Special thanks for support from **FEMA**, **WV DHSEM**, and **The Polis Center** at Indiana University–Purdue University Indianapolis



CONTENT

Overview	1
Key Flood Analysis Findings	2
General Description of County and Communities	3
Building Inventory	3
Creating the Building Inventory from Tax Assessor Data	4
Generating Hazus GBS and UDF from Building Inventory	5
Building Exposure to Potential Hazards	6
Building Exposure - General Building Stock (GBS)	6
Building Exposure in Floodplain - User Defined Facilities (UDF)	9
Inventory of Facilities and Community Assets	11
Essential Facilities	11
Critical Facilities	11
Community Assets	12
Inventory of Mitigated Properties	13
Flood Layer Inputs for Flood Model	14
1% Annual Chance Flood Hazard Area	14
Water Depth Grid	14
Riverine Flood Hazards Assessment	15
Riverine 1% Flood Building Damages	15
Riverine 1% Flood Debris Generation	22
Riverine 1% Flood Shelter Requirements	24
Data Deliverables to County	26
Maps	26
GIS Data	26
Integration of County Flood Risk Results in the State Hazard Mitigation Plan	27
Appendix A: Building Inventory Processing	29
Appendix B: Work Flow Diagram for Flood Risk Assessments	30
Appendix C: Data Gap Analysis	31
Appendix D: Statewide Risk Assessment Objectives	32
Appendix E: Multi-Hazard Risk Assessment Lifecycle	34
Appendix F: Statewide Spatial Integration of Surface Tax Parcels	36
Appendix G: 3D Flood Risk Visualization	37

Appendix H:	Glossary of Risk Assessment	nt Terminology	
-------------	-----------------------------	----------------	--

TABLES

Table 1:	Local Building Inventory4
Table 2A:	Countywide/Community Building Count and Exposure (\$) from General Building Stock
Table 2B:	Countywide Building Count and Exposure (\$) from CAMA Building Appraisal Values7
Table 3A:	Morgan County Flood Hazard Building Exposure in 1% Annual Chance Floodplain9
Table 3B:	Berkeley Springs Flood Hazard Building Exposure in 1% Annual Chance Floodplain9
Table 3C:	Paw Paw Flood Hazard Building Exposure in 1% Annual Chance Floodplain.
Table 4:	Essential Facilities
Table 5:	Critical Facilities
Table 6:	Community Assets
Table 7:	Mitigated Properties13
Table 8:	Morgan County Riverine Floodplain (1% Flood) Related Losses16
Table 9:	High Potential Loss Structures
Table 10:	Buildings, Essential Facilities, Critical Facilities, and Community Assets Damaged (1% Flood) \dots 17
Table 11:	Debris Summary Report
Table 12:	Shelter Requirements Summary Report
Table 13:	State Level Integration of Food Risk Data
Table A-1:	CAMA Records Query of February 201629
Table A-2:	Building Inventory Processing performed on 2015 data29
Table A-3:	E-911 Addressable Structures
Table C-1:	Data Gap Analysis for Region 9 PDC Counties

FIGURES

Figure 1:	Flood Model Overview.	1
Figure 2:	Hazus GBS and UDF Inventory Data.	5
Figure 3:	Sample Map of Countywide General Building Stock Exposure by Census Block	8
Figure 4:	Zoomed-in View of parcel centroid based UDF Structures (blue dots) in Flood Zone	. 10
Figure 5:	Zoomed-in View of Water Depth Grid	. 14
Figure 6A:	Morgan County (1% Flood) Damaged Building Losses	. 18
Figure 6B:	Berkeley Springs Community (1% Flood) Damaged Building Losses	. 19
Figure 6C:	Paw Paw Community (1% Flood) Damaged Building Losses	. 20
Figure 7:	Facilities and Community Assets in 1% Annual Chance Floodplain	. 21
Figure 8:	Riverine 1% Flood Debris Weight (Tons)	. 23
Figure 9:	Riverine 1% Flood Shelter Requirements (individual short term needs)	. 25
Figure 10:	Hazus Level 1 Food Risk Layers in WV Flood Tool	. 27
Figure B-1:	Work Flow Diagram for Flood Risk Assessments	. 30
Figure E-1:	Multi-Hazard Risk Assessment Lifecycle	. 35
Figure F-1:	Statewide Spatial Integration of Surface Tax GIS Parcels for Agency and Public Benefit.	. 36
Figure G-1:	WV Flood Tool information for Sample 3D Site	. 38
Figure G-2:	Google Earth View of Sample 3D Site	. 39
Figure G-3:	3D Rendering Showing Flood Depth and Flooded Structures	. 39

Morgan County Flood Risk Assessment Report

Overview

A riverine flood risk assessment was conducted to assist Morgan County to quantify and visualize the potential loss resulting from a 1% annual chance flood event.¹ First, all buildings and critical facilities in the county exposed to potential hazards were inventoried. From tax parcel and assessment data a detailed building inventory with engineered replacements costs was created for the entire county. A user defined facilities (UDF) data set was created by filtering the countywide building inventory to exclude points outside the 1% annual chance flood area. Next, the general and UDF building inventory to exclude points outside the 1% annual chance flood hazard inundation area were imported into the Hazus-MH (Version 2.2) flood risk modeling software. A flood depth raster layer was generated within Hazus and analyzed with the building inventories, DEM and flood hazard area to estimate building damages, debris, and people displaced (Figure 1). Flood Model results for each county will be integrated into the 2018 State Hazard Mitigation Plan and the Risk MAP View of the WV Flood Tool (www.mapwWV.gov/Flood).




Figure 1: Flood Model Overview. The Flood Model uses the best available site-specific building data, flood hazard area, elevation and water depth grid to estimate building damages, debris, and people displaced for a 1% annual chance flood event. A more detailed flow diagram is available in Appendix B.

Morgan Flood Risk Report

¹A one percent annual chance flood event (a.k.a. 100-year flood) has a one percent (1 in 100) chance of being equaled or exceeded during any given year. See the Appendix G glossary for further information.

Key Flood Analysis Findings

Using Hazus modeling software, the flood risk analysis for a 1% annual chance flood event for Morgan County resulted in the following findings:

EXPOSURE OF BUILDINGS & PROPERTIES TO FLOODING

- **Building Exposure in County:** In Morgan County a minimum of 9,735 parcels with buildings have an aggregate total replacement value of 2 billion (2010 dollars).
- **Building Exposure in Flood Hazard Area:** A total of 625 buildings in the flood hazard area are exposed to flood damage which have an aggregate total replacement value of 152 million dollars.
- Facilities Exposure: A total of 19 essential facilities, 26 critical facilities, and 32 community assets are exposed to potential hazards. Replacement costs were generally not computed for essential, critical or community asset facilities. At least one school building, and several church buildings are located within the 1% annual chance flood area. Only those facilities for which spatial data are available from the West Virginia Division of Homeland Security and Emergency Management were analyzed.
- Mitigated Properties: None shown in Morgan County in current data.

FLOOD MODEL RESULTS

- Countywide Flood Loss Estimates
 - Physical Building Damage: Based on the water depth and inundation area, the Hazus Flood Model estimates physical damage to 615 buildings in Morgan County at a replacement cost of 60 million dollars. Commercial properties have the highest loss ratio of 6.9%. Two critical facilities (school and fire station) and four churches are located in the 1% annual chance flood hazard area. The community of Berkeley Springs has the highest potential loss structures.
 - **Building Debris Generation**: An estimated 16,350 tons of building debris would be generated and require 654 truckloads (@25 tons/truck) to remove.
 - **Direct Social Losses**: Displaced households due to loss of housing habitability represent 984 individuals, of which 229 will require short term publicly provided shelter.
- Berkeley Springs Community Building Damage: The Hazus Flood Model estimates physical damage to 91 buildings in Berkeley Springs at a replacement cost of 7.7 million dollars. Commercial properties have the highest loss ratio of 11.8%. At least one essential facility, a fire department, is located in the 1% annual chance flood hazard area.

- Paw Paw Community Building Damage: The Flood Model estimates physical damage to 34 buildings in Morgan County at a replacement cost of 3 million dollars. Agricultural properties have the highest loss ratio of 17.6%. No essential or critical facilities are located in the flood hazard area.
- Individual Building Damage: The structure in the flood hazard zone with the highest building loss is a commercial property located at Harrison Avenue and Independence Street, Berkeley Springs. The Hazus estimated building loss for this property is 672 thousand dollars.

General Description of County and Communities

County Description: The geographical size of **Morgan County** is 230 square miles and contains 1,206 census blocks. The region contains over 7,000 households and has a total population of 17,541 people (2010 Census Bureau data). There are an estimated 9,735 parcels in the region with a total building replacement value (excluding contents) of 2,059 million dollars (2010 dollars). Approximately 81.9% of the buildings (and 66.8% of the building value) are associated with residential housing.

Berkeley Springs Description: The town of **Berkeley Springs** is an incorporated community exposed to periodic flooding. The geographical size of the community is less than one square mile and contains 70 census blocks. The region is home to 624 people (2010 Census Bureau data). There are an estimated 411 parcels with buildings in the region with a total building replacement value (excluding contents) of 115 million dollars (2010 dollars).

Paw Paw Description: The town of **Paw Paw** is an incorporated community exposed to periodic flooding. The geographical size of the community is 1 square mile and contains 44 census blocks. Paw Paw has a total population of 508 people (2010 Census Bureau data). There are an estimated 34 parcels with buildings in the region with a total building replacement value (excluding contents) of 10 million dollars (2010 dollars).

Building Inventory

Two locally produced GIS data sets – county assessor tax surface parcels and E-911 addressable structures – were used to create and validate the local building inventory. From tax parcel and assessment data a detailed building inventory with engineered replacements costs was created for the entire county. The parcel-based building inventory identified **9,735** structures while the E-911 database listed **16,491** addressable structures. Table 1 identifies the number of structures in the county and towns of Berkeley Springs and Paw Paw. More information about the building inventory is described below.

Creating the Building Inventory from Tax Assessor Data

The building inventory for Morgan County was created from assessor records and GIS parcels. The CAMA records were extracted from the centralized State Tax Department's Integrated Assessment System while the GIS parcels were provided by the Morgan County Assessor's Office. Key inventory attribute fields for modeling flood damage included occupancy class or land use (LUC), building condition (GRADE), construction type (EXTWALL), foundation type and first floor height (BASMT), stories (STORIES), year built (YRBLT), structure area (AREASUM) and building costs (DWELVAL, COMVAL, OBYVAL).

Before the CAMA records are joined to the GIS parcels, a number of processing steps were performed on the CAMA records. First, all the CAMA records were reduced to single, unique records associated with the primary structure of the particular parcel. *Note that this action eliminated multiple valued structures or trailer courts listed on the same parcel.* Second, the CAMA records were classified by the LAND USE as residential, commercial, industrial, agricultural, religious, government, education, and unknown buildings. Unknown records typically represent land use codes for vacant or exempt properties, although some of these records may contain appraisal values. In addition, parcel records with invalid land use codes were deleted. During this processing step the CAMA records with null values for key engineering values were dropped. For example, since assessor records may not have values for the parcels that are not taxable, certain parcels with tax-exempt government, religious, education, or other non-profits structures may have been deleted. For Morgan County this refinement process resulted in the source CAMA records of 15,454 being decreased to 10,828 records (Tables 1 and A-2). Lastly, the "improved" or "processed" 10,828 CAMA records were then joined by the unique parcel identifier with the centroids of each parcel polygon to create the spatially referenced **building inventory**.

Assessor Records and Parcels				E-911 Sites	
Category	Parcel CAMA Records (unique)	Improved or Processed CAMA Records (attributes)	Assessor Parcels (parcel polygons)	Building Inventory (parcel centroids + CAMA replacement cost attributes)	E-911 Addressable Structures (points on structure)
Berkeley Springs	-	-	527	411	511
Paw Paw			99	259	351
Unincorporated	-	-	14,828	9,065	15,629
Total	15,454	10,828	15,039	9,735	16,491

Table 1: Local Building Inventory

Based on the spatial join of the GIS parcels and CAMA records, the match rate between the GIS parcel-based building inventory (9,736) and the processed CAMA records (10,828) for Morgan County was **90%**. Further

research should be conducted to improve the match rate between the assessor CAMA records and GIS parcels.

As a cross-reference check for the completeness of the parcel-based building inventory, the E-911 addressable structures for Morgan County were extracted from the Statewide Addressing and Mapping System maintained by WV DHSEM. The match rate between the GIS parcel-based building inventory (9,736) and E-911 addressable structures (16,491) was **59%, a low rate because numerous structures in the E-911 database are uninhabitable structures and have no address**. See Appendix A for more information about the match rates and other statistics in creating the building inventory.

Generating Hazus GBS and UDF from Building Inventory

To import the building inventory into the Hazus-MH loss estimation software, the building inventory data is processed for two formats: **General Building Stock** (aggregate data) and **User Defined Facilities** (site-specific data). The General Building Stock (GBS) contains the least amount of detail and is stored as data that has been aggregated by census tract or block, whereas User Defined Facilities (UDF) contain basic characteristics about individual buildings. Both the GBS and UDF data layers contain building characteristics (occupancy class, square footage, building type, foundation, year built, etc.) to determine the **building replacement costs.** Note that the replacement costs for both the GBS inventory and UDF inventory should match. Lastly, the GBS is used for the debris and people evacuation models while the UDF is needed for the detail flood loss analysis of structures in the 1% annual chance flood hazard area.




Figure 2: Hazus GBS and UDF Inventory Data. The General Building Stock (aggregate buildings) and User Defined Facilities (individual buildings) are derived from the Building Inventory.

Building Exposure - General Building Stock (GBS)

The **General Building Stock** (GBS) is updated in Hazus-MH with the local building inventory prior to running the Flood Model loss analysis scenarios. Table 2A lists all the buildings in the county that are exposed to potential hazards. The number of buildings and full replacement costs based on standardized engineering cost calculations are listed by specific occupancy classes. Table 2B lists similar information but was derived from the appraised building values directly queried from the assessor records database.

Based on engineering calculation estimates there are **9,735 parcels with buildings** in the county which have an aggregate total replacement value of **2 billion dollars** (2010 dollars). *Note that this cost was calculated for one primary structure per parcel and does not account for multiple valued structures in the same parcel.* Figure 3 shows a map representation by census block geographical units of the GBS building assets exposed to potential hazards.

Occupancy Classification Building Count		Total Building Exposure (\$)	Percent of Total			
	Morgan County (including all jurisdictions)					
Residential	7,971	1,375,697,425	66.79%			
Commercial	877	308,882,657	15.00%			
Industrial	86	145,824,422	7.08%			
Agricultural	713	159,486,816	7.74%			
Religious	74	53,230,099	2.58%			
Government	8	1,987,453	0.10%			
Education	6	14,542,194	0.71%			
TOTAL	9,735	\$2,059,651,066	100.00%			
	Berkeley	/ Springs				
Residential	288	58,654,641	51.06%			
Commercial	107	44,533,677	38.77%			
Industrial	0	0	0.00%			
Agricultural	0	0	0.00%			
Religious	13	8,759,736	7.63%			
Government	2	499,958	0.44%			
Education	1	2,423,699	2.11%			
TOTAL	411	\$114,871,711	100.0%			
	Paw	Paw				
Residential	195	33,549,178	83.9%			
Commercial	44	16,585,541	14.3%			
Industrial	6	11,336,982	1.6%			
Agricultural	3	742,641	0.0%			
Religious	8	5,115,848	0.2%			
Government	2	499,958	0.0%			
Education	1	2,423,699	0.0%			
TOTAL	259	\$70,253,847	100.0%			


 Table 2A:
 Countywide/Community Building Count and Exposure (\$) from General Building Stock

General		Appraised	
Occupancy	Count	Building Costs	CAMA Land Use Codes
Agricultural	807		112-113
		53,918,900.00	
Commercial	939		109-110, 310, 319-360, 362-390, 393-99,
		82,314,800.00	602, 610-11, 630, 640, 670, 690, 701-706,
			710-723
Education	8		612-13
		30,834,500.00	
Government	9		603,660
		1,587,900.00	
Industrial	98		391-92, 400-471, 707
		7,446,600.00	
Religious	79		361, 620, 680
		17,394,900.00	
Residential	8,857	988,522,400.00	101-108, 115, 201-213, 301, 314-318
Unknown	4,656		100, 114,123, 300, 600, 601, 604, 700
		16,685,600.00	
Invalid Codes	1		900
Total	15,454	\$1,198,705,600	

Table 2B: Countywide Building Count and Exposure (\$) from CAMA Building Appraisal Values

In Table 2B The CAMA building appraisal values (APRBLG) were also categorized by occupancy class and for the county summed to 1.2 billion dollars. The appraised building layer is for reference purposes only and not used in the Flood Model analysis.

Figure 3: Sample Map of Countywide General Building Stock Exposure by Census Block. Replacement building costs are aggregated to Census Blocks. Darker block fill color indicates higher exposure amount. Floodplain (1% annual chance) in black hatch. Building Inventory points are represented as blue squares.



Building Exposure in Floodplain - User Defined Facilities (UDF)

User Defined Facilities (UDF), point representations of buildings that are in the 1% annual chance flood zone, were imported into the Hazus-MH Flood Model. Before the UDF structures are imported into Hazus-MH to execute the Flood Model, it is possible to adjust the site-specific data, visually or through GIS analysis, to building structures using E-911 addressable sites, building footprints, leaf-off aerial photography, or other reference layers. This step was not carried out in Morgan County due to time and data constraints. The high number of address points in Table 1, when compared with CAMA derived improvements, indicate that some structures with E-911 addresses are not dwellings, businesses or other structures normally considered in flood risk assessment. A random visual check of address points and structure type appears to confirm this suggestion.

Table 3A:Morgan County Flood Hazard Building Exposure in 1% Annual Chance Floodplain. Data inputof choice is User Defined Facilities.

General Occupancy	UDF Count	Exposure in Floodplain
		(Total Replacement Costs using UDF)
Agricultural	34	7,675,869
Commercial	158	60026829
Education	0	0
Government	1	249979
Industrial	10	16989562
Religious	5	3013700
Residential	417	63746525
TOTAL	625	151,702,464

A total of **625 buildings** at a replacement cost of **\$151,702,464** are exposed to a 1% annual chance flood event in **Morgan County** (Table 3A). The flood loss estimates are calculated from the subset of building inventory modeled in Hazus as User Defined Facilities, or site-specific points. During the flood model runs the flood damage is estimated in percent and is weighted by the area of inundation at a given water depth for an individual structure. Refer to Table 8 to view the estimated building damages resulting from the Flood Model.

Table 3B:Berkeley Springs Flood Hazard Building Exposure in 1% Annual Chance Floodplain. Datainput of choice is User Defined Facilities.

General Occupancy	UDF Count	Exposure in Floodplain
		(Total Replacement
		Costs using UDF)
Agricultural	0	0
Commercial	48	20,460,683
Education	0	0
Government	0	0
Industrial	0	0
Religious	4	2,736,784
Residential	39	8,067,094
TOTAL	91	31,264,561

Table 3C: Paw Paw Flood Hazard Building Exposure in 1% Annual Chance Floodplain. Data input of choice is User Defined Facilities.

General Occupancy	UDF Count	Exposure in Floodplain (Total Replacement Costs using UDF)
Agricultural	2	495,094
Commercial	14	6,139,708
Education	0	0
Government	0	0
Industrial	0	0
Religious	0	0
Residential	18	3,436,036
TOTAL	34	10,070,838

A total of **91 buildings** at a cost of **\$31,264,561** are exposed to a 1% annual chance flood event in **Berkeley Springs** (Table 3B). Refer to Table 8 to view the estimated building damages resulting from the Flood Model.

A total of **34 buildings** at a cost of **\$10,070,838** are exposed to a 1% annual chance flood event in **Paw Paw** (Table 3C). Refer to Table 8 to view the estimated building damages resulting from the Flood Model.

Figure 4: Zoomed-in View of parcel centroid based UDF Structures (blue dots) in Flood Zone



Inventory of Facilities and Community Assets

Essential facilities, critical facilities, and community assets were compiled from various GIS stewards and should be validated with the local communities. Replacement costs were not computed for facilities and community assets for this study. If replacement costs of non-profit buildings are unavailable, then costs may be obtained from:

- Various websites for some facilities
- Insurance records for individual buildings
- Calculated from square footage by using RS Means replacement

Essential Facilities

Essential facilities are defined as those that are vital to the county in the event of a hazard. These include police departments, fire stations, schools, health care facilities, and emergency service zones. The WV DHSEM compiles essential facilities from various local, state, and federal data sources.

Table 4: Essential Facilities

Category	Number of Facilities
Police Stations	4
Fire Stations	4
Emergency Service Centers	1
Health Care Facilities	1
Schools	9
TOTAL	19

Critical Facilities

Critical facilities are buildings that are deemed economically or socially viable to the county and is a superset of essential facilities. The following critical facilities were inventoried and mapped for Morgan County.

Table 5: Critical Facilities

Category	Number of Facilities	Description
Governmental Facilities Courthouses 	1	Essential for the delivery of critical services and crisis management including data and communication centers and key government complexes.
Dams	18	Source: USACE, GNIS. Holiday Lake Dam in VA not included.
Transportation Systems Airports Railroads Bridges 	1 1 5	Necessary for transport of people and resources including airports, highways, railways. Source: GNIS
Lifeline Utility Systems Wastewater Treatment Plants Potable Water Systems Communication Facilities Electric Substations Electric Power Facilities Natural Gas Facilities 	n/a n/a n/a n/a n/a	Vital to public health and safety including potable water, wastewater, oil, natural gas, electric power, and communication systems.
Hazardous Material Facilities	n/a	Involved in the production, storage, and/or transport of corrosives, explosives, flammable materials, radioactive materials, and toxins.
TOTAL	26	

Community Assets

The Morgan County Mitigation Planning team may identify facilities that are significant to the county; for example, historic landmarks or significant tourist attractions. These facilities or structures are referred to as **community assets**.

Table 6: Community Assets

Category	Number of Facilities	Notes
Churches	32	GNIS
Government Office	n/a	
Hazmat Non Facility	n/a	
Mobile Home and Campground	n/a	
Polling Place	n/a	
Emergency Shelter	n/a	
Water Tower	n/a	
Poultry Slaughtering Stations	n/a	
TOTAL	32	

Inventory of Mitigated Properties

Both FEMA and WVDHSEM have worked together to identify buyouts of repetitive flood properties since the inception of FEMA HMA grant programs during the past two decades. Morgan County has no **mitigated properties** shown in currently available data.

Table 7: Mitigated Properties

Category	Mitigated Properties
Berkeley Springs	0
Paw Paw	0
Unincorporated	0
TOTAL	0

Flood Layer Inputs for Flood Model


Important flood layers for the Flood Model include the 1% annual chance flood hazard area and water depth grid.


1% Annual Chance Flood Hazard Area

The 1% annual chance floodplain in Morgan County was used to run all the flood model scenarios. The **flood hazard area** was downloaded from FEMA's National Flood hazard Layer (NFHL) digital database.

Water Depth Grid

A **water depth grid** was required to estimate the percentage of physical damage to a structure weighted by the area of inundation at a given depth. The Hazus Enhanced Quick Look tool was used to generate a depth grid for the flood analysis based on the FEMA National Flood Hazard Layer and the digital elevation model at 1/3 arc-second (approximately 10 m) resolution downloaded from the USGS National Elevation Dataset (NED). Although certain counties in West Virginia may have more accurate depth grids generated from HEC-RAS computer modeling software for the Approximate A Zones, these HEC-RAS depth grids were not available for Morgan County. New depth grids are expected to be available statewide over the next several years.





The depth grid range for Morgan County is from 0 to 47 feet.

Riverine Flood Hazards Assessment

Riverine flooding is the number one natural hazard risk in West Virginia. Riverine floodplains in the State typically are narrow, confined channels in the steep valleys of hilly and mountainous areas. The volume of water in the floodplain is a function of the size of the contributing watershed and topographic characteristics such as watershed shape and slope, and climatic and land-use characteristics.

Both Hazus-MH and GIS software were used to model flood building damages, debris estimations, and the number of shelters required for the displaced population. Below are the tables and maps from running the Flood Model for a 1% annual chance flood event. Hazus-MH loss estimates may be impacted by certain assumptions and process variances made in this flood risk assessment. The Morgan County analysis used Hazus Version 2.2 and the population counts were derived from the 2010 Census. During the flood model runs the flood damage is estimated in percent and is weighted by the area of inundation at a given depth for a given census block (GBS input) or user-defined structure (UDF input).

Riverine 1% Flood Building Damages

Buildings in Morgan County are vulnerable to flooding from the 1% Riverine Flood (also known as the 1% annual chance flood) and the cost to rebuild may have significant consequences to the community. Hazus-MH estimated the 1%-annual-chance flood would physically damage **615 buildings** at a replacement cost of **59.8 million dollars** for Morgan County. In the Berkeley Springs community, the Flood Model estimated damage to **91 buildings** at a replacement cost of **7.7 million dollars**. In Paw Paw an estimated **34 buildings** will be damaged at a replacement cost of **2.9 million dollars**.

The flood loss estimates for damaged buildings by community and occupancy class are listed in Table 8. Table 8 also provides the loss ratios (Total Building Loss / Total Building Exposure) for the county and jurisdictions. The loss ratios were computed by dividing the Total Building Loss (Table 8) by the Total Building Exposure (Table 2A). **Commercial properties** have the highest loss ratio of **6.9%** and **11.8%** for Morgan County and the Berkeley Springs community, respectively. In the Paw Paw community, **agricultural properties** have the highest loss ratio at **17.6%**.

The structure in the flood hazard zone with the highest total replacement cost is a **commercial property** valued at **947 thousand dollars** located at Harrison Avenue and Independence Street, Berkeley Springs. The Hazus estimated loss for this property is **672 thousand dollars**. Table 9 lists a sample of five individual damaged structures in the county based on replacement costs.

Table 10 lists all the buildings, essential facilities, critical facilities, and community assets damaged in a 1% annual chance flood event. Figures 6A through 6C are maps of the flood damaged buildings in Morgan County and the communities of Berkeley Springs and Paw Paw. A large-format county map of the flood damaged buildings is provided with this report. Figure 7 is a map of facilities /community

assets of Berkeley Springs community affected by the 1% annual chance flood. There are a total of **six facilities** located in the 1% flood hazard area: 1 school, 1 courthouse, 1 fire department and 4 churches.

	Number of		Total Building			
0	Buildings	Total Building	Exposure (\$) in	D. D. dia		
Classification	Damaged	Loss (\$)	Jurisdiction	Loss Ratio		
	Morgan Co	unty (including all ju				
Residential	413	27,562,062	1,375,697,425	2.00%		
Commercial	158	21,353,161	308,882,657	6.91%		
Industrial	10	8,171,979	145,824,422	5.60%		
Agricultural	29	2,551,472	159,486,816	1.60%		
Religious	4	199,033	53,230,099	0.37%		
Government	1	3,828	1,987,453	0.19%		
Education	0	0	14,542,194	0.00%		
TOTAL	615	\$59,841,535	\$2,059,651,066			
		Berkeley Springs				
Residential	38	2,330,862	58,654,641	3.97%		
Commercial	48	5,244,835	44,533,677	11.78%		
Industrial	1	0,211,000	0	0.00%		
Agricultural	0	0	0	0.00%		
Religious	4	161,452	8,759,736	1.84%		
Government	0	0	499,958	0.00%		
Education	0	0	2,423,699	0.00%		
TOTAL	91	\$7,737,149	\$114,871,711			
		Paw Paw				
Residential	18	1,366,114	33,549,178	4.07%		
Commercial	14	1,502,459	16,585,541	9.06%		
Industrial	0	0	11,336,982	0.00%		
Agricultural	2	130,479	742,641	17.57%		
Religious	0	0	5,115,848	0.00%		
Government	0	0	499,958	0.00%		
Education	0	0	2,423,699	0.00%		
TOTAL	34	\$2,999,052	\$70,253,847			

Table 8: Morgan County Riverine Floodplain (1% Flood) Related Losses

Table 9: High Potential Loss Structures

#	E-911 Street Address	City	Zip Code	Parcel ID	Building Type	Building Loss ¹
Building 1	Harrison Ave & Independence St	Berkeley Springs	25411	03 1A003300000000	Commercial	\$671,628
Building 2	N Mercer St & Independence St	Berkeley Springs	25411	03 1A003200000000	Commercial	\$373,585
Building 3	3077 Valley Rd	Berkeley Springs	25411	02 11000900010000	Commercial	\$342,009
Building 4	Independence & Mercer Streets	Berkeley Springs	25411	03 1A001700000000	Commercial	\$287,123
Building 5	167 Indian Run Ln (New home)	Berkeley Springs	25411	08 2A005900000000	Residential	\$253,600

¹ Building Content Loss often exceeds Building Loss.

 Table 10:
 Buildings, Essential Facilities, Critical Facilities, and Community Assets Damaged (1% Flood)

Category	Building Inventory	Essential Facilities	Critical Facilities	Community Facilities	Total Structures
Berkeley Springs	37	0	1	4 ³	38
Paw Paw	34				34
Unincorporated	544	1 ²	0	0	545
TOTAL STRUCTURES	615	1 school	1 courthouse	4 churches	617

¹Note that while one fire department building is located in the floodplain, damages for the structure were not modeled.

²At least one school facility, south of Berkeley Springs, lies in the 1% chance flood area.

³Churches are not part of the total tally since they are included in the "religious" category of the building inventory (Table 8).

There are **617 structures** in the 1% Annual Chance flood, including 1 school, 1 courthouse, and 4 churches. The building and facility inventories should be verified by local authorities.




Figure 6A: Morgan County (1% Flood) Damaged Building Losses



Figure 6B: Berkeley Springs Community (1% Flood) Damaged Building Losses






Figure 6C: Paw Paw Community (1% Flood) Damaged Building Losses





Riverine 1% Flood Debris Generation

Debris disposal can be a significant issue following floods. The Hazus Flood Model estimates debris from building damage during floods, including building finishes, and structural components. The physical damage estimates are not made for building contents, or for bridges or other lifelines.

The Hazus Flood Model debris estimation methodology determines the expected amounts of debris generated at various depths of water and reported at the census block level. Output from this module is the debris weight (in tons). The classes of debris are defined as follows: (1) building finishes (carpeting, dry wall, insulation, etc.), (2) structural components (wood, brick, etc.) and (3) foundation materials (concrete slab, concrete block, rebar, etc.). This distinction is made because of the different types of material handling equipment required to handle the debris. For more information about the Hazus Flood Model debris estimation methodology refer to the Hazus-MH Technical Manual.

The Flood Model estimates that a total of **16,350 tons** of debris will be generated. Of the total amount, Finishes comprises 19% of the total, Structure comprises 40% of the total (Table 11). If the debris tonnage is converted into an estimated number of truckloads, it will require **654 truckloads** (@25 tons/truck) to remove the debris generated by the flood. The results are mapped in Figure 8.

Table 11: Debris Summary Report

Morgan County	Finishes	Structures	Foundations	Total Tons
Debris Tons	3,157	6,467	6,727	16,350

As can be expected, the results of the debris flood model reflect that in the event of a 1% annual chance flood, emergency response officials will need to target resources for removing debris along the flooded waterways in proximity to populated places. Refer to the debris map for more specific information and for mitigation planning.




Figure 8: Riverine 1% Flood Debris Weight (Tons)

Riverine 1% Flood Shelter Requirements

A significant part of any planning scenario is to estimate the number of individuals who will need to be sheltered in the short-term. The direct social loss of the displaced population is based on the inundation area and depth of flooding. Flood sheltering needs are based on the displaced population, not the damage state of the structure.

The Hazus-MH Flood Model determines the number of individuals likely to use government-provided short-term shelters through determining the number of displaced households as a result of the flooding. To determine how many of those households and the corresponding number of individuals will seek shelter in government-provided shelters the number is modified by factors accounting for income and again by factors accounting for age. For more information about the Hazus Flood Model shelter estimation methodology refer to the Hazus-MH Technical Manual.

Hazus 2.2 Report: For Morgan County, **984** individuals will be displaced, **229** of whom require short term publicly provided shelter (Table 12). The results are mapped in Figure 9.

 Table 12:
 Shelter Requirements Summary Report

Morgan County	Number of Displaced People	Number of People Needing Short Term Shelter
	984	229

The results of the shelters requirements model reflect that in the event of a 1% annual chance flood, emergency response officials will need to organize shelters near the flooded communities. Refer to the flood shelter requirements map for more specific information and for planning temporary housing needs.




Figure 9: Riverine 1% Flood Shelter Requirements (individual short term needs)

Data Deliverables to County

In addition to this report, the following maps and GIS data layers are available to the counties.

Maps

- Building Exposure
- Physical damage map of buildings and facilities (large size)
- Debris map
- Population Displacement / Shelter map
- Select 3D maps (if building footprints available)
- Miscellaneous maps

GIS Data

- GIS parcel polygons
- E-911 Addressable Structures
- Building Inventory
- UDF Floodplain Structures
- Essential Facilities
- Critical Facilities
- Community Assets
- Mitigated Properties (not available for Morgan County at this time)
- Hazus-MH .hpr files (available on request)

Integration of County Flood Risk Results in the State Hazard Mitigation Plan

Results of the county flood risk assessment will be used to update the 2018 State Hazard Mitigation Plan and the Risk MAP View of the WV Flood Tool (www.mapWV.gov/Flood). Table 11 lists the flood risk data layers involved in integrating county flood risk studies to regional and state levels.




Figure 10: Hazus Level 1 Food Risk Layers in WV Flood Tool

Table 13: State Level Integration of Food Risk Data. The following hazard risk information from counties can be integrated at the regional and state levels for the State Hazard Mitigation Plan. The **boldfaced** loss estimates are currently in the WV Flood Tool and based on a statewide Hazus Level 1 analysis performed several years ago.

Flood Risk Data	Inventory Type	Spatial Representation				
** Flood Model INPUTS **						
Total Assets Exposed: Number and exposure (\$) of all buildings	Building Inventory	Parcel Centroids or Census Tracts/Blocks				
Floodplain Exposure: Number and exposure of buildings located in the Special Flood Hazard Area (SFHA)	UDF	Parcel centroids can be spatially adjusted with E-911 addressable structures				
Facilities Exposure: Essential Facilities, Critical Facilities, Community Assets	GIS Infrastructure Databases	Usually Points				
Mitigated Properties: (shown currently in Expert View of WV Flood Tool)	Mitigated Properties	Polygons				
Water Depth Grid	 Hazus-generated (EQL) Advisory Flood Height Detailed Flood Zone (FIS) 	Raster				
Flood Hazard Area	DFIRMs	Polygons				
** Flo	od Model OUTPUTS **					
Total Loss: Number and value (\$) of Buildings and Contents damaged in Hazus Level 2 analysis	UDF & GBS	PointsCensus Tracts/BlocksWatersheds				
Total Building Loss: Number and value (\$) of damaged buildings in Hazus Level 2 analysis. Loss Ratios as calculated from the Hazus Analysis	UDF & GBS	 Points Census Tracts/Blocks Watersheds 				
Total Debris costs (\$)	GBS	Census Tracts/Blocks				
Total Shelter: People requiring shelter	GBS	Census Tracts/Blocks				

Appendix A: Building Inventory Processing

CAMA Field	Value
County ID	33
Name	Morgan
Appraised Land Value	498,611,400
Appraised Building Value	1,198,705,600
Appraised Total Value	1,697,317,000
Total Unique Parcel Records	15,454

Table A-1: CAMA Records Query of February 2016

Table A-2: Building Inventory Processing performed on 2015 data


File Type	Count	Notes
CAMA Records (attributes)	15,454	CAMA records are reduced to a single, unique primary property record
Improved CAMA Records (attributes)	10,828	CAMA codes transformed to values recognized by Hazus. For Morgan County the source CAMA data included 15,454 records. The destination data – Improvements records included 10,828 records. This means that that there were 4,626 failed records and research by Polis showed that these included records without DWELVAL, COMVAL and OBYVAL values. It also included records with LUC values (100, 114, 123, 200, 300, 600, 601 604,700) for vacant and exempt lands which were deemed inappropriate for the desired modeling purposes.
Assessor Parcels (parcel polygons)	15,039	GIS parcel polygon file provided by county and converted to parcel centroid points. Total parcel polygons equals 15,039.
Building Inventory (parcel centroids + attributes)	9,735	Join between parcel centroid points and Improved CAMA records yielded 9,735 building points
CAMA - parcel match rate	90%	Building Inventory (9,735) divided by Improved CAMA record attributes (10,828) = 90%

Table A-3: E-911 Addressable Structures

File Type	Count	Notes
Addressable Sites	16,491	Addressable structures for Morgan County from Statewide Addressing and Mapping System (SAMS).
E-911 – parcel match rate	59%	Parcel-centroid building inventory (9,735) divided by Addressable sites (16,491) = 59%

Appendix B: Work Flow Diagram for Flood Risk Assessments

Figure B-1: Work Flow Diagram for Flood Risk Assessments.



Appendix C: Data Gap Analysis

The spatial E-911 addresses for Morgan County are not accurate or complete and should be prioritized for future data improvement efforts. In addition, the aerial imagery for Morgan County is more than five years old and thus should be updated. It would also be beneficial if Morgan County had building footprints to generate photorealistic 3D flood visualization maps. More coordination is required with local and state emergency offices to identify available geodatabases for essential facilities, critical facilities, and community assets.

DATA LAYERS	Berkeley County	Morgan County	Jefferson County
IAS/CAMA Tables	2014	2015	2015
Tax Parcels	2015	2016	2016
E-911	2013	2015 (FAIL)	2016
Building Footprints	2008	NONE	2015
Aerial Imagery	2016	2010 (POOR)	2016
Water Depth Grid	No Advisory Flood	No Advisory	Advisory Flood
	Heights	Flood Heights	Heights available
Elevation	No complete Lidar	No complete	Complete Lidar
	coverage	Lidar coverage	Coverage
Critical	Incomplete	Incomplete	Incomplete
Infrastructure			

Table C-1: Data Gap Analysis for Region 9 PDC Counties

Long-term objectives for risk assessments in West Virginia:

- Establish a communication and training network for exchanging risk assessment information and technical skills among local, state, federal, and other entities. Multi-agency coordination and data exchange among organizations allow for comprehensive risk assessment for communities. A multihazard Risk Assessment Lifecycle should be applied to regularly evolving risk assessment studies.
- Exchange the best available risk assessment data among local, state, and federal geo-platforms. Incorporate historical flood data into risk assessment studies. Use online map validation tools for local communities to validate risk assessment data.
- 3) Create a statewide inventory of all **buildings and facilities exposed** (with replacement costs) in flood hazard, dam/levee failure, and landslide susceptibility zones.
- 4) Create a consistent statewide water depth grid (FEMA Risk MAP Studies + Model-Backed Zone A Studies + FIS conversion / water surface elevations from x-sections of detailed studies) using available high-resolution elevation data for 1% Annual Chance Floods. The depth grids are important for (1) water depth visualization in the WV Flood Tool and for (2) calculating physical building damage costs using Hazus-MH flood loss software.
- 5) Perform county-level risk assessments for 55 counties:
 - a) **Flood risk assessments** for riverine 1% annual chance flood based on Hazus-MH flood loss estimates using water depth and flood inundation area inputs
 - i) *Physical Building Damage Assessments*: Create a statewide inventory of structures at risk to physical building damage
 - ii) *Flood Debris Generated* (debris removal)
 - iii) Flood Shelter Requirements (temporary housing)
 - b) Dam and levee failure flood inundation assessments (USACE led)
 - i) Prioritize dam inspections in accordance with risk and those that do not have an EAP digitized
 - ii) Integrate Dam and Levee safety action class (class 1 5) for every USACE dam and levee into HIRA and THIRA.
 - iii) Produce documentaries about/on aging dam structures around endangered communities (Develop a list of potential dams on which to focus).
 - iv) Create a task force to address levee safety in West Virginia (Coordination between NRCS and USACE on levee safety issues).
 - c) Landslide susceptibility studies
 - i) Generate county-level landslide risk maps and structures at risk
 - ii) With partners create a statewide landslide incident inventory

- 6) Review and identify **data gaps** for key GIS data layers for risk assessment studies (parcels, addresses, imagery, elevation, flood layers, critical infrastructure, etc.). Provide recommendations to the appropriate organizations to improve data management and governance.
- 7) Publish risk assessment reports for local and state hazard mitigation plans.
- 8) Publish **input and output model data** associated with risk assessments on state and federal geoplatforms.
- 9) Upload 2D/3D flood risk and dam failure maps to the RiskMAP View of the WV Flood Tool (www.mapWV.gov/Flood). Provide a web planning tool to estimate physical building damage, debris removal, and temporary shelter needs. This flood risk assessment information permits communities or individual property owners to decide how to allocate resources for the most effective and efficient response and recovery, and to prioritize mitigation measures to reduce future loss.

Multi-Hazard Risk Assessment Lifecycle for West Virginia:

1) Data Management and Governance

- a) Govern organizations and procedures to develop statewide data layers and web services (parcels, addresses, imagery, elevation, levee/dams, water depth grids, critical infrastructure, etc.). Periodically publish WV Framework Report about status of State's Spatial Data Infrastructure.
- b) Manage data flows of key local data sets from county assessor offices (parcels and CAMA) and E-911 offices (addresses).
- c) Oversee timely integration of local data (parcels, E-911) to state-level geodatabases by data stewards.
- d) Manage statewide GIS parcel integration with CAMA data extracts and site addresses for Building Inventory and other risk assessment products.
- e) Coordinate development of landslide hazard occurrence database with appropriate agencies.
- f) Determine feasibility of GIS data development projects through State Hazard Mitigation Office.
- g) Govern risk assessment studies through State Hazard Mitigation Office and Regional Planning and Development Councils.

2) Coordination

- a) Identify key stakeholders (geographers, geologists, engineers, planners, soil scientists, GIS specialists, decision makers, private consultants) at county, state, and federal agencies and other organizations. Maintain an experts' knowledge database.
- b) Set up communication services: email listserv, web portal, etc.
- c) Organize and conduct risk assessment training.
- d) Coordinate closely data and project priorities with federal (FEMA, USACE, USGS, NRCS, EPA), state (WV DHSEM, WV OGC, WV Tax), region (PDCs), and local (assessor, E-911) offices. Leverage stakeholders to prioritize and rectify critical data gaps.
- e) Continuously review and amend Hazard Mitigation Grant applications to development consistent and comprehensive risk assessment products at the local level which in turn can be integrated into regional and statewide assessments.
- f) Encourage regions to begin the actual process of updating their hazard mitigation plans a minimum of one year in advance, preferably two years before the expiration date.

3) Data Collection

- a) Collect data inputs for risk assessment studies.
- b) Review historical flood data resources.
- c) Utilize online web viewers for collecting and validating building inventory and critical infrastructure data sets.

4) Data Processing

- a) Create general and specific building inventories (total assets exposed) inputs.
- b) Develop accurate water depth grids and flood inundation boundaries.

5) Analysis

- a) Execute Flood Risk Models for each county and community.
 - i) Flood Risk Models using Hazus-MH software
 - (1) Building Damage Flood Model
 - (2) Debris Model
 - (3) Shelter Model
 - ii) Dam/Levee Failure Flood Inundation Models
- b) Execute Geological Hazard Models for each county and community.
 - i) Landslide Susceptibility
 - ii) Karst Hazards

6) Interpret and Publish Results

- a) Publish supplemental risk assessment reports (flood, landslides, etc.) for each county.
- b) Publish results to state and federal geo-platforms: WV Flood Tool, FEMA RiskMAP, state and federal data clearinghouses, etc.
- c) Integrate county risk assessments to regional and state level.
- d) Identify and prioritize GIS data and risk assessment strategies at county, region, and state levels.

7) Inform Local Decisions

- a) Provide knowledge transfer services via reports, data exchange, meetings, conferences, etc.
- b) Provide regions with the technical skills to perform their own risk assessment analysis studies so don't have to depend on outside consultants.

Figure E-1: Multi-Hazard Risk Assessment Lifecycle. Courtesy of Cynthia McCoy, FEMA Region 10.



Appendix F: Statewide Spatial Integration of Surface Tax Parcels

The surface tax GIS parcels are an integral part multi-hazard risk assessments since the GIS parcels combined with building characteristics of the assessment data generate the estimated building replacement costs. E-911 addresses can be joined to the tax parcels to further pin-point the structure's site location and physical address.

Tax assessor data is formatted in ArcGIS software before updating the GBS and UDF inventories. The primary spatial field should be addresses instead of parcel polygon centroids unless a parcel has multiple addresses such as a trailer court.




Figure F-1: Statewide Spatial Integration of Surface Tax GIS Parcels for Agency and Public Benefit.

Appendix G: 3D Flood Risk Visualization

3D map products were created for a test location in Berkeley County in order to enhance the communication of flood risk to structures in the 1% annual chance floodplain. Similar 3D maps can also be created for Morgan County if building footprints are available.

Figure G-1 shows the results of a query in the West Virginia Flood Tool (WV Flood Tool) for the sample site on Baltimore Street in Martinsburg. The ground elevation and 1% annual chance flood Base Flood Elevation (BFE) indicate a depth of at least 1 foot of flood water at the site. How this will affect the building depends on whether or not the foundation is elevated above local BFE, and, if so, by how much.

A Google Earth view of the site is shown in **Figure G-2** for reference. Vertical representation is poor and buildings appear flattened or otherwise distorted. The use of solid shapes will reduce this problem.

The 3D rendering in **Figure G-3** shows the site structure highlighted in light blue surrounded by the anticipated depth of the 1% annual chance flood. Affected structures are indicated in red. Attributes for the highlighted structure appear at the bottom of the screen.





Figure G-1: WV Flood Tool information for Sample 3D Site

Figure G-2: Google Earth View of Sample 3D Site (Looking northwest)



Figure G-3: 3D Rendering Showing Flood Depth and Flooded Structures (Red)



1% Annual Chance Flood: A one percent annual chance flood event (a.k.a. 100-year flood) has a one percent (1 in 100) chance of being equaled or exceeded during any given year. The one percent annual chance flood was selected in the early 1970s when the National Flood Insurance Program was tasked with mapping all floodplains in the U.S. It was considered a reasonable balance of protection and cost between the 0.5% (1 in 200) to 0.2% (1 in 500) variable reference used at the time by the U.S. Army Corps of Engineers for floodwater control structure design. The term 100 year (or 5 year or 500 year) refers to the expected frequency of return of a given flood event. The area of inundation associated with a given flood event is called the **floodplain** (e.g. 1% floodplain, etc.).

Source: The 100 Year Flood Myth, Federal Emergency Management Agency, Region 10, handout.

CAMA/IAS: Computer Assisted Mass Appraisal (CAMA) is the process of using a computer to assist in property tax appraisal and equity evaluation. Administered by the Tax Commissioner, the CAMA system for West Virginia is a centralized Oracle database also known as the Integrated Assessment System (IAS). A number of years ago the State Tax Department purchased real estate mass appraisal software called IAS. This software is installed on the network server in Charleston and is accessed through computers in each County Assessor's Office.

Advisory Flood Heights: The water surface elevation (WSEL), in feet, of the 1% annual chance (100-year) flood at a given location, as determined using hydrology and hydraulics (H&H) analysis and the best available elevation data. Add 5 feet to this value to allow for accuracy issues. This information is currently available for approximately 12% of the West Virginia counties.

http://www.mapwv.gov/flood/content/documents/AFHhandout.pdf

Mitigated Properties: Properties and land parcels located within floodplains that experience frequent flooding and damage due to flood events, may be altered, purchased, or have deed restrictions placed upon them by FEMA, in an effort to prevent loss of life and property damage. Property owners/communities with public lands in floodplains are compensated for their land, and the land usually becomes public green space. (<u>FEMA link</u>) (<u>Youtube</u>)

See more flood definitions at http://mapwv.gov/flood/resources.html